

View Online at <https://aerobasegroup.com/nsn/5930-01-330-8617>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.188 inches

Overall Height:

Between 10.173 inches and 10.773 inches

Overall Width:

Between 2.690 inches and 2.930 inches

Body Height:

Between 2.630 inches and 2.870 inches

Unthreaded Mounting Hole Diameter:

Between 0.250 inches and 0.310 inches

Longest Horizontal Distance Between Mounting Centers:

Between 2.350 inches and 2.470 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.600 inches and 0.720 inches

Longest Vertical Distance Between Mounting Centers:

Between 3.220 inches and 3.340 inches

Temperature Sensing Element Type:

Bulb

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

0.5 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

53.00 actuation point degrees fahrenheit and 48.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0