## NSN 5930-01-330-8619

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-330-8619

| Body Style:  |
|--|
| Hole mounted   |
| Hazardous Locations/environmental Protection:                                      |
| Dustproof and oiltight and watertight  |
| Overall Height:  |
| 3.062 inches   |
| Actuator Style:  |
| Round  |
| Actuator Height:   |
| 0.500 inches   |
| Housing Height:  |
| 2.500 inches   |
| Housing Length:  |
| 7.062 inches   |
| Housing Width:   |
| 2.250 inches   |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length:  |
| 6.812 inches   |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:   |
| 1.688 inches   |
| Maximum Voltage Rating In Volts:   |
| 600.0 ac and 250.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Nonpile-up Contact Arrangement:  |
| 1 two circuit, double break/double make, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:                              |
| 1.500 amperes resistive dc and 5.000 amperes resistive ac                          |
| Precious Material And Location:  |
| Contacts silver  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A053a0   |