

View Online at <https://aerobasegroup.com/nsn/5930-01-330-8693>

Thread Length:

0.660 inches single pressure connection

Overall Length:

2.740 inches

Outside Diameter:

0.250 inches single connection

Body Length:

1.370 inches

Overall Diameter:

0.880 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.938 inches

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Line

Contact Action Stimulus:

Decrease

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

7.0 amperes resistive load single voltage and 4.0 amperes inductive load single voltage and 2.5 amperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

150.00 actuation point pounds per square inch and 100.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Specification Data:

30003-1771as673 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0