

View Online at <https://aerobasegroup.com/nsn/5930-01-330-8775>

Overall Length:

Between 2.630 inches and 2.750 inches

Outside Diameter:

0.250 inches single connection

Overall Diameter:

Between 1.088 inches and 1.125 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 1.088 inches and 1.125 inches

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Line

Contact Action Stimulus:

Decrease

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage and 250.0 milliamperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+3.00/+45.00 actuation point pounds per square inch

Contact Stimulus Rating:

30.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level fourth voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

50.0 second voltage and 60.0 second voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Specification Data:

54933-105437 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0