

View Online at <https://aerobasegroup.com/nsn/5930-01-330-8775>

**Overall Length:**

Between 2.630 inches and 2.750 inches

**Outside Diameter:**

0.250 inches single connection

**Overall Diameter:**

Between 1.088 inches and 1.125 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

Between 1.088 inches and 1.125 inches

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Line

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

500.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage and 250.0 milliamperes inductive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+3.00/+45.00 actuation point pounds per square inch

**Contact Stimulus Rating:**

30.00 actuation point pounds per square inch

**Contact Voltage Rating In Volts:**

30.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Frequency In Hertz:**

50.0 second voltage and 60.0 second voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt single pressure connection

**Specification Data:**

54933-105437 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0