

View Online at <https://aerobasegroup.com/nsn/5930-01-330-8776>

Inside Diameter:

0.250 inches single connection

Overall Length:

5.000 inches

Overall Height:

2.310 inches

Overall Width:

4.000 inches

Body Length:

2.750 inches

Unthreaded Mounting Hole Diameter:

Between 0.260 inches and 0.300 inches

Longest Horizontal Distance Between Mounting Centers:

3.250 inches

Shortest Horizontal Distance Between Mounting Centers:

1.625 inches

Longest Vertical Distance Between Mounting Centers:

3.310 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load fifth voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

30.00 actuation point pounds per square inch gage and 25.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

80.0 ac at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Specification Data:

54933-106104 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0