

View Online at <https://aerobasegroup.com/nsn/5930-01-330-8776>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

5.000 inches

**Overall Height:**

2.310 inches

**Overall Width:**

4.000 inches

**Body Length:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.260 inches and 0.300 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.250 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.625 inches

**Longest Vertical Distance Between Mounting Centers:**

3.310 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

500.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load fifth voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

30.00 actuation point pounds per square inch gage and 25.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

80.0 ac at sea level third voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 third voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Specification Data:**

54933-106104 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0