

View Online at <https://aerobasegroup.com/nsn/5930-01-330-9243>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Humidity resistant

Overall Length:

1.340 inches

Overall Height:

3.650 inches

Overall Width:

1.660 inches

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

1.340 inches

Body Width:

1.660 inches

Body Height:

Between 1.080 inches and 1.120 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.400 inches and 0.440 inches

Actuator Height:

Between 1.120 inches and 1.160 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and out and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 screw

Specification Data:

96906-ms24660 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0