

View Online at <https://aerobasegroup.com/nsn/5930-01-331-0548>

**Overall Length:**

1.765 inches

**Overall Height:**

1.795 inches

**Overall Width:**

1.150 inches

**Unthreaded Mounting Hole Diameter:**

0.030 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.595 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Lever all actuators

**Features Provided:**

Rfi shielding

**Contact Voltage Rating In Volts:**

50.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

100.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 1 (a), 11(b), 12(c), 13(d), 14(e), 15(f) each section

**Contact Arrangement Truth Table:**

Binary with common not-true bits, 2 pole - 16 positions each section

**Color:**

White each indicator marking

**Precious Material And Location:**

Contacts and printed circuit board circuit surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0