

View Online at <https://aerobasegroup.com/nsn/5930-01-331-0548>

Overall Length:

1.765 inches

Overall Height:

1.795 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.030 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.595 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Lever all actuators

Features Provided:

Rfi shielding

Contact Voltage Rating In Volts:

50.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 1 (a), 11(b), 12(c), 13(d), 14(e), 15(f) each section

Contact Arrangement Truth Table:

Binary with common not-true bits, 2 pole - 16 positions each section

Color:

White each indicator marking

Precious Material And Location:

Contacts and printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0