

View Online at <https://aerobasegroup.com/nsn/5930-01-331-4752>

Overall Length:

2.937 inches

Overall Diameter:

1.306 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

8 each section periphery

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.25 amperes resistive load dc at sea level and 250.00 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-3786f specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-3786/4h government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0