

View Online at <https://aerobasegroup.com/nsn/5930-01-331-9770>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

Between 0.720 inches and 0.780 inches

Overall Height:

Between 1.250 inches and 1.430 inches

Overall Width:

Between 0.720 inches and 0.780 inches

Body Length:

Between 0.650 inches and 0.710 inches

Body Width:

Between 0.650 inches and 0.710 inches

Body Height:

Between 0.970 inches and 1.030 inches

Actuator Length:

Between 0.580 inches and 0.640 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.160 inches and 0.220 inches

Actuator Width:

Between 0.580 inches and 0.640 inches

Actuator Color:

Green single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

Open single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

T-1 lamp bulb size

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0