

View Online at <https://aerobasegroup.com/nsn/5930-01-332-0681>

Body Style:

Bushing mount

Overall Length:

Between 0.490 inches and 0.510 inches

Overall Height:

Between 1.346 inches and 1.426 inches

Overall Width:

Between 0.260 inches and 0.280 inches

Bushing Length:

Between 0.340 inches and 0.360 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.260 inches and 0.280 inches

Body Height:

Between 0.340 inches and 0.360 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

Between 0.521 inches and 0.541 inches

Actuator Width:

Between 0.065 inches and 0.085 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0