

View Online at <https://aerobasegroup.com/nsn/5930-01-332-0681>

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.490 inches and 0.510 inches

**Overall Height:**

Between 1.346 inches and 1.426 inches

**Overall Width:**

Between 0.260 inches and 0.280 inches

**Bushing Length:**

Between 0.340 inches and 0.360 inches

**Body Length:**

Between 0.490 inches and 0.510 inches

**Body Width:**

Between 0.260 inches and 0.280 inches

**Body Height:**

Between 0.340 inches and 0.360 inches

**Case Material:**

Plastic

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.521 inches and 0.541 inches

**Actuator Width:**

Between 0.065 inches and 0.085 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Contact and terminal surfaces silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0