NSN 5930-01-332-2232

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-332-2232

| Body Style: |
|---|
| Bushing mounted |
| Overall Length: |
| 1.375 inches |
| Overall Height: |
| 0.615 inches |
| Overall Width: |
| 0.765 inches |
| Bushing Length: |
| 0.300 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.270 inches |
| Body Height: |
| 0.450 inches |
| Case Material: |
| Plastic |
| Actuator Length: |
| 0.450 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.360 inches |
| Actuator Width: |
| 0.450 inches |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 3.000 amperes resistive ac

NSN 5930-01-332-2232

Push Switch - Page 2 of 2



| Special I | Features: |
|-----------|-----------|
|-----------|-----------|

Also includes black sap-in frame to put around actuator

Precious Material And Location:

Terminal surfaces and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0