NSN 5930-01-332-4013

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-332-4013 **Thread Class:** 2a **Body Style: Bushing mount Overall Length:** 0.510 inches **Overall Height:** 1.290 inches **Overall Width:** 0.510 inches **Bushing Length:** 0.320 inches **Body Length:** 0.510 inches **Body Width:** 0.510 inches **Body Height:** 0.450 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Diameter:** 0.120 inches **Actuator Height:** 0.270 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Printed circuit and threaded bushing **Features Provided:** Mounting hardware Thready Qty Per Inch (tpi): 40 **Thread Size:**

Nonpile-up Contact Arrangement:

0.250 inches

2 pole, double throw, both positions maintained single switch unit

NSN 5930-01-332-4013

Toggle Switch - Page 2 of 2



Contact	I oad	Current	Rating	Δt	Maximum	Rated	Voltage:
Contact	Luau	Current	Naumy	\neg	WIGNIIII	Nateu	VOILAGE.

3.000 amperes resistive ac and 4.000 amperes resistive dc

Precious Material And Location:

Terminal surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0