## NSN 5930-01-332-4506



Push Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-01-332-4506 **Body Style: Bushing mounted Body Diameter:** Between 0.615 inches and 0.650 inches **Bushing Length:** 0.360 inches **Body Length:** 1.290 inches **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.270 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 2.000 amperes resistive dc and 1.500 amperes inductive dc and 0.500 amperes lamp dc **Test Data Document:** 81349-mil-prf-22885/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 8 tab, solder lug **Specification Data:** 81349-mil-prf-22885/18 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-std (military Standard): Mil-prf-22885 spec.

A053a0