

View Online at <https://aerobasegroup.com/nsn/5930-01-332-7439>

Thread Class:

2a single mounting facility

Thread Length:

0.360 inches single mounting facility and 0.390 inches single mounting facility

Overall Length:

3.359 inches

Overall Height:

Between 1.834 inches and 1.854 inches

Overall Width:

Between 1.427 inches and 1.447 inches

Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.798 inches single actuator and 0.828 inches single actuator

Nonturn Device Radius:

0.516 inches at 3: 00 o'clock and 0.546 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

2 1st section rear

Throw Quantity:

13 2nd section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Dummy terminal

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 1st section

Switch Actuator Indexing Position Quantity:

13 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

25.7 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor blade surface silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0