

View Online at <https://aerobasegroup.com/nsn/5930-01-332-8455>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.510 inches

**Overall Height:**

1.212 inches

**Overall Width:**

0.580 inches

**Bushing Length:**

Between 0.260 inches and 0.270 inches

**Body Length:**

0.510 inches

**Body Width:**

0.465 inches

**Body Height:**

0.440 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.100 inches and 0.110 inches

**Actuator Height:**

Between 0.257 inches and 0.287 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**End Application:**

Tactical air operations module an/tyq-2 (v) 1

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Special Features:**

Unthreaded bushing; terminals bent at right angle for pcb mounting

**Test Data Document:**

81349-mil-dtl-83731/16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 printed circuit

**Specification Data:**

81349-mil-dtl-83731/16 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0