

View Online at <https://aerobasegroup.com/nsn/5930-01-332-8455>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.510 inches

Overall Height:

1.212 inches

Overall Width:

0.580 inches

Bushing Length:

Between 0.260 inches and 0.270 inches

Body Length:

0.510 inches

Body Width:

0.465 inches

Body Height:

0.440 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.100 inches and 0.110 inches

Actuator Height:

Between 0.257 inches and 0.287 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

Tactical air operations module an/tyq-2 (v) 1

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Unthreaded bushing; terminals bent at right angle for pcb mounting

Test Data Document:

81349-mil-dtl-83731/16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 printed circuit

Specification Data:

81349-mil-dtl-83731/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0