

View Online at <https://aerobasegroup.com/nsn/5930-01-332-9430>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.620 inches

Overall Height:

0.750 inches

Overall Width:

Between 0.740 inches and 0.760 inches

Body Width:

Between 0.670 inches and 0.690 inches

Body Height:

0.750 inches

Actuator Length:

Between 0.600 inches and 0.620 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.180 inches and 0.200 inches

Actuator Width:

Between 0.600 inches and 0.620 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Actuator Inscription:

Lamp test single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

1.440 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

White actuator inscription appears yellow when illuminated

Terminal Type And Quantity:

11 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0