

View Online at <https://aerobasegroup.com/nsn/5930-01-333-2195>

**Thread Class:**

2b 1st mounting facility

**Thread Length:**

0.420 inches 2nd mounting facility and 0.460 inches 2nd mounting facility

**Overall Length:**

Between 6.280 inches and 6.400 inches

**Overall Height:**

Between 2.790 inches and 2.830 inches

**Overall Width:**

Between 2.790 inches and 2.830 inches

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

2.280 inches 1st mounting facility and 2.320 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.280 inches 1st mounting facility and 2.320 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 1st mounting facility

**Thread Size:**

0.625 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unef 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0