

View Online at <https://aerobasegroup.com/nsn/5930-01-333-2195>

Thread Class:

2b 1st mounting facility

Thread Length:

0.420 inches 2nd mounting facility and 0.460 inches 2nd mounting facility

Overall Length:

Between 6.280 inches and 6.400 inches

Overall Height:

Between 2.790 inches and 2.830 inches

Overall Width:

Between 2.790 inches and 2.830 inches

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

2.280 inches 1st mounting facility and 2.320 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.280 inches 1st mounting facility and 2.320 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.625 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0