## NSN 5930-01-333-2438

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-333-2438

## **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Shock resistant

## **Overall Length:**

3.280 inches

## **Overall Height:**

2.500 inches

#### **Overall Width:**

3.000 inches

## Individual Section Quantity:

4

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Facility Circle Radius:**

1.156 inches single mounting facility

#### **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### Features Provided:

Actuator knob and dummy section

## Thready Qty Per Inch (tpi):

24 single mounting facility

#### **Thread Size:**

0.190 inches single mounting facility

## **Contact Voltage Rating In Volts:**

120.0 dc at sea level

## **Mounting Facility Pattern:**

Four position circular single mounting facility

## Switch Actuator Indexing Position Quantity:

3 single actuator

## **Terminal Type:**

Tab w/screw

## **Contact Switching Action:**

Breaks before makes each section periphery

## **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

10.0 amperes inductive load dc at sea level and 10.0 amperes resistive load dc at sea level

#### Style Designator:

Tap, circuit selector

# NSN 5930-01-333-2438

Rotary Switch - Page 2 of 2



Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

