

View Online at <https://aerobasegroup.com/nsn/5930-01-333-4287>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.297 inches single mounting facility and 0.327 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

3.348 inches

**Overall Height:**

Between 2.320 inches and 2.531 inches

**Overall Width:**

Between 2.320 inches and 2.531 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.658 inches single actuator and 0.718 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 12:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 12:00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+6.000/+10.000 inch-pounds single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load highest ac voltage rating at sea level

**Style Designator:**

Square wafer, panel mount

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Specification Data:**

81349-mil-s-3786/40 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0