NSN 5930-01-333-8904

Hazardous Locations/environmental Protection:

Flow Switch - Page 1 of 2

Corrosion resistant
Overall Length:
4.937 inches
Overall Height:
1.750 inches



View Online at https://aerobasegroup.com/nsn/5930-01-333-8904

Overall Width:
1.000 inches
Body Length:
4.125 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
2.375 inches
Operating Tempurature Rating:
Between -20.0 degrees fahrenheit and 300.0 degrees fahrenheit
Mounting Method:
Base and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
1 pole, double throw, one position momentary
1 pole, double throw, one position momentary Terminal Type:
1 pole, double throw, one position momentary Terminal Type: Wire lead
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating:
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability:
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range:
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +0.13/+1.50 actuation point gallons per minute
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +0.13/+1.50 actuation point gallons per minute Contact Adjustment Type:
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +0.13/+1.50 actuation point gallons per minute Contact Adjustment Type: Internal actuation point screw
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +0.13/+1.50 actuation point gallons per minute Contact Adjustment Type: Internal actuation point screw Contact Stimulus Rating:
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +0.13/+1.50 actuation point gallons per minute Contact Adjustment Type: Internal actuation point screw Contact Stimulus Rating: 0.03 actuation point gallons per minute
1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 80.0 milliamperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +0.13/+1.50 actuation point gallons per minute Contact Adjustment Type: Internal actuation point screw Contact Stimulus Rating: 0.03 actuation point gallons per minute Contact Voltage Rating In Volts:

NSN 5930-01-333-8904

Flow Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0