NSN 5930-01-333-8922

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-333-8922

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.188 inches
Body Length:
0.500 inches
Body Width:
0.200 inches
Body Height:
0.470 inches
Unthreaded Mounting Hole Diameter:
0.087 inches
Actuator Style:
Round
Actuator Diameter:
0.083 inches
Actuator Height:
0.030 inches
Actuator Free Position Height:
0.320 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.004 overtravel inches and 0.003 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc
Precious Material And Location:
Contact surfaces gold
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a

NSN 5930-01-333-8922

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0