

View Online at <https://aerobasegroup.com/nsn/5930-01-334-6713>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

3.234 inches

**Overall Height:**

1.200 inches

**Overall Width:**

0.960 inches

**Body Width:**

0.800 inches

**Body Height:**

1.200 inches

**Actuator Length:**

1.040 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.140 inches

**Actuator Width:**

0.800 inches

**Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color:**

Green single actuator and yellow single actuator

**Actuator Inscription:**

Steady strobe single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator yellow lower half of actuator green

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

3.094 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:**

Complete p/n 10ha30c1f171j14 (yygg) m2n301r7n1steady/strobe

**Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0