NSN 5930-01-334-6713

Push Switch - Page 1 of 2

inductive ac and 1.500 amperes lamp ac

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-334-6713

Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
3.234 inches
Overall Height:
1.200 inches
Overall Width:
0.960 inches
Body Width:
0.800 inches
Body Height:
1.200 inches
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Green single actuator and yellow single actuator
Actuator Inscription:
Steady strobe single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator yellow lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.094 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes

NSN 5930-01-334-6713

Push Switch - Page 2 of 2



Complete p/n 10ha30c1f171j14 (yygg) m2n301r7n1steady/strobe

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0