

View Online at <https://aerobasegroup.com/nsn/5930-01-334-9748>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.500 inches

Overall Height:

1.275 inches

Overall Width:

0.353 inches

Bushing Length:

0.250 inches

Body Length:

0.500 inches

Body Width:

0.260 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.500 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

6625-01-255-4248 test set, cable shield resistance

Mounting Surface To Terminal End Distance:

0.525 inches

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 3.000 amperes resistive ac

Special Features:

Unthreaded bushing; terminal mounted

Precious Material And Location:

Contact and terminal surfaces silver

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0