

View Online at <https://aerobasegroup.com/nsn/5930-01-334-9749>

**Body Style:**

Panel mount

**Overall Length:**

0.715 inches

**Overall Height:**

1.105 inches

**Overall Width:**

0.475 inches

**Body Length:**

0.500 inches

**Body Width:**

0.270 inches

**Body Height:**

0.495 inches

**Case Material:**

Plastic

**Actuator Length:**

0.362 inches

**Actuator Style:**

Pivoted

**Actuator Height:**

0.203 inches

**Actuator Width:**

0.450 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Arleigh burke class ddg, nimitz class cvn, ticonderoga class cg (47), oliver perry class ffg. Calibration standards equipment.

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Precious Material And Location:**

Terminal surfaces and contacts silver

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

28480-3101-2915 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0