NSN 5930-01-335-4370

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-335-4370
Hazardous Locations/environmental Protection:
Shock proof and watertight
Overall Length:
4.450 inches
Overall Height:
6.300 inches
Overall Width:
3.700 inches
Unthreaded Mounting Hole Diameter:
0.230 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.700 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Flange single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
480.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes inductive load lowest dc voltage rating at sea level
Special Features:
Legend plate reads stop run; plastic and glass polyester inclosure
Style Designator:
Tap, circuit selector

N/a

Shelf Life:

NSN 5930-01-335-4370Rotary Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A052b0