Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-335-4370

Hazardous Locations/environmental Protection: Shock proof and watertight **Overall Length:** 4.450 inches **Overall Height:** 6.300 inches **Overall Width:** 3.700 inches **Unthreaded Mounting Hole Diameter:** 0.230 inches single mounting facility **Individual Section Quantity:** 1 Longest Horizontal Distance Between Mounting Centers: 2.000 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 5.700 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical **Mounting Method:** Flange single mounting facility and unthreaded hole single mounting facility **Features Provided:** Actuator knob and legend plate **Contact Voltage Rating In Volts:** 480.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Terminal Type:** Screw **Switch Actuator Positioning Increment:** 90.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 10.0 amperes inductive load lowest dc voltage rating at sea level **Special Features:** Legend plate reads stop run; plastic and glass polyester inclosure Style Designator: Tap, circuit selector Shelf Life: N/a

## **NSN 5930-01-335-4370** Rotary Switch - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0

