# NSN 5930-01-335-4925

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-335-4925

# **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Waterproof

# **Overall Length:**

1.200 inches

#### **Overall Height:**

2.930 inches

#### **Overall Width:**

0.960 inches

#### **Body Length:**

1.100 inches

# **Body Width:**

0.960 inches

# Body Height:

Louy noight

# 2.790 inches

Case Material:

Metal

### Actuator Length:

1.040 inches

#### Actuator Style:

Rectangular

#### Actuator Height:

0.140 inches

#### Actuator Width:

0.800 inches

#### Actuator Color:

White single actuator

#### Illuminated Actuator Color:

Amber single actuator

#### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

# **Features Provided:**

Rfi shielding

# Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac

# NSN 5930-01-335-4925

Push Switch - Page 2 of 2



Precious Material And Location:

Contacts silver

# Terminal Type And Quantity:

12 turret and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0