## NSN 5930-01-335-8084

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-335-8084

**Thread Class:** 

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

**Overall Length:** 

4.440 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.437 inches single actuator

**Overall Diameter:** 

1.150 inches

**Individual Section Quantity:** 

inai 7

**End Application:** 

Control console part number 300774 onboard 210 ft wmec coast guard vessels

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Pole Quantity:** 

2 each section periphery

**Throw Quantity:** 

4 each section periphery

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-01-335-8084

Rotary Switch - Page 2 of 2



Breaks before makes each section periphery

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

6.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0