

View Online at <https://aerobasegroup.com/nsn/5930-01-335-8950>

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

4.450 inches

Overall Height:

6.300 inches

Overall Width:

3.700 inches

Unthreaded Mounting Hole Diameter:

0.230 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.700 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Flange single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

480.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

1 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes inductive load lowest dc voltage rating at sea level

Special Features:

Legend plate reads stop; plastic and glass polyester inclosure

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0