

View Online at <https://aerobasegroup.com/nsn/5930-01-335-8950>

**Hazardous Locations/environmental Protection:**

Shock proof and watertight

**Overall Length:**

4.450 inches

**Overall Height:**

6.300 inches

**Overall Width:**

3.700 inches

**Unthreaded Mounting Hole Diameter:**

0.230 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.700 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Flange single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Contact Voltage Rating In Volts:**

480.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

1 single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes inductive load lowest dc voltage rating at sea level

**Special Features:**

Legend plate reads stop; plastic and glass polyester inclosure

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0