

View Online at <https://aerobasegroup.com/nsn/5930-01-336-1766>

**Thread Class:**

2a 2nd mounting facility

**Thread Length:**

0.250 inches 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.290 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.100 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.340 inches single actuator

**Overall Diameter:**

0.600 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**End Application:**

5810-01-283-1394 t enc dev kg 194a

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded bushing w/panel seal 2nd mounting facility

**Thread Size:**

0.250 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+5.000/+12.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

100.0 milliamperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Decimal, 1 pole - 12 positions single section

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unef 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0