

View Online at <https://aerobasegroup.com/nsn/5930-01-336-1766>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.250 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.290 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.100 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.340 inches single actuator

Overall Diameter:

0.600 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

End Application:

5810-01-283-1394 t enc dev kg 194a

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing w/panel seal 2nd mounting facility

Thread Size:

0.250 inches 2nd mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+5.000/+12.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level

Contact Arrangement Truth Table:

Decimal, 1 pole - 12 positions single section

Style Designator:

Snap or line

Thread Series Designator:

Unef 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0