NSN 5930-01-336-1767

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-336-1767

Thread Class:

2b 1st mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

0.580 inches

Overall Height:

1.645 inches

Overall Width:

1.730 inches

Distance Between Mounting Facility Centers:

1.437 inches 1st mounting facility

Individual Section Quantity:

1

Operating Tempurature Range:

-30.0/+85.0 degrees celsius

Mounting Method:

Printed circuit 2nd mounting facility

Actuator Type:

Push button all actuators

Features Provided:

Illuminated and rfi shielding

Thready Qty Per Inch (tpi):

56 1st mounting facility

Thread Size:

0.086 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 1st mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions single section

Color:

White single lamp

NSN 5930-01-336-1767

Code Indicating Wheel Switch - Page 2 of 2



Stv	e	Des	ian	ato	r:
,	_		. 9.		

Rectangular indicating

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0