

View Online at <https://aerobasegroup.com/nsn/5930-01-336-1768>

**Thread Class:**

2b 1st mounting facility

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

0.510 inches

**Overall Height:**

1.953 inches

**Overall Width:**

Between 1.670 inches and 1.730 inches

**Distance Between Mounting Facility Centers:**

1.427 inches 1st mounting facility and 1.447 inches 1st mounting facility

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-30.0/+85.0 degrees celsius

**Mounting Method:**

Printed circuit 2nd mounting facility

**Actuator Type:**

Push button all actuators

**Features Provided:**

Illuminated and rfi shielding

**Thready Qty Per Inch (tpi):**

56 1st mounting facility

**Thread Size:**

0.086 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

12 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 0, 1, 2, 3, 0, 1, 2, 3 single section

**Contact Arrangement Truth Table:**

Binary code, 1 pole - 12 positions single section

**Color:**

White single lamp

**Style Designator:**

Rectangular indicating

**Thread Series Designator:**

Unc 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0