

View Online at <https://aerobasegroup.com/nsn/5930-01-336-1769>

Thread Class:

2b 1st mounting facility

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

0.510 inches

Overall Height:

1.953 inches

Overall Width:

Between 1.670 inches and 1.730 inches

Distance Between Mounting Facility Centers:

1.427 inches 1st mounting facility and 1.447 inches 1st mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-30.0/+85.0 degrees celsius

Mounting Method:

Printed circuit 2nd mounting facility

Actuator Type:

Push button all actuators

Features Provided:

Illuminated and rfi shielding

Thready Qty Per Inch (tpi):

56 1st mounting facility

Thread Size:

0.086 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 1st mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions single section

Color:

White single lamp

Style Designator:

Rectangular indicating

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0