## NSN 5930-01-336-2313

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-336-2313

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.050 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

#### . . . . . .

Actuator Length:

0.530 inches

## Actuator Style:

Rectangular

#### **Actuator Height:**

0.100 inches

#### Actuator Width:

0.530 inches

#### Actuator Color:

White single actuator

#### **Actuator Inscription:**

Propn system fail single actuator single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

#### Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## **Features Provided:**

Full display lens

### Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

#### **Precious Material And Location:**

Contact surfaces silver



# NSN 5930-01-336-2313

Push Switch - Page 2 of 2



Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0