NSN 5930-01-336-3019

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5930-01-336-3019
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.050 inches
Body Width:
0.620 inches
Body Height:
0.620 inches
Actuator Length:
0.600 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.600 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes
inductive ac and 1.000 amperes lamp ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
17 socket, integrated wire termination
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-336-3019

Push Switch - Page 2 of 2



Fiig:

A053a0