NSN 5930-01-336-4705

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-336-4705
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.050 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.530 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.530 inches
Actuator Color:
White single actuator
Actuator Inscription:
Motor room bilge single actuator single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes
inductive ac and 1.000 amperes lamp ac

Precious Material And Location: Contact surfaces silver

NSN 5930-01-336-4705

Push Switch - Page 2 of 2



Tarminal	Type	And C	Quantity:
rerminai	i vbe	Ana v	zuantity.

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0