## NSN 5930-01-336-4714

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-336-4714

| Dody Chyle.  |
|--|
| Body Style: Panel mounted                                  |
| Hazardous Locations/environmental Protection:              |
|  |
| Explosion proof and humidity resistant                     |
| Overall Length:  |
| 3.050 inches   |
| Overall Height:  |
| 0.750 inches   |
| Overall Width:   |
| 0.750 inches   |
| Body Width:  |
| 0.750 inches   |
| Body Height:   |
| 0.750 inches   |
| Case Material:   |
| Metal  |
| Actuator Length:   |
| 0.530 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.100 inches   |
| Actuator Width:  |
| 0.530 inches   |
| Actuator Color:  |
| White single actuator                                      |
| Actuator Inscription:                                      |
| Mn hyd power plant lo pres single actuator single actuator |
| Maximum Voltage Rating In Volts:                           |
| 28.0 dc and 115.0 ac                                       |
| Mounting Surface To Terminal End Distance:                 |
| 2.950 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Features Provided:   |
| Full display lens  |
| Contact Load Current Rating At Maximum Rated Voltage:      |

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

**Precious Material And Location:** 

inductive ac and 1.000 amperes lamp ac

Contact surfaces silver

## NSN 5930-01-336-4714

Push Switch - Page 2 of 2



| Termina | I Type         | And (  | Quantit | ٧. |
|---------|----------------|--------|---------|----|
|         | 11 1 1 1 1 1 1 | Allu ' | wuanni  | ν. |

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0