NSN 5930-01-336-7686

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-336-7686

The state of the s	
Body Style:	
Bushing mounted	
Hazardous Locations/environmental Protection:	
Humidity resistant	
Overall Length:	
0.957 inches	
Overall Height:	
Between 0.350 inches and 0.370 inches	
Overall Width:	
Between 0.350 inches and 0.370 inches	
Body Diameter:	
Between 0.350 inches and 0.370 inches	
Bushing Length:	
Between 0.240 inches and 0.260 inches	
Body Length:	
0.500 inches	
Case Material:	
Metal	
Actuator Diameter:	
Between 0.175 inches and 0.195 inches	
Actuator Height:	
Between 0.157 inches and 0.217 inches	
Actuator Color:	
Green single actuator	
Illuminated Actuator Color:	
Green single actuator	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Thready Qty Per Inch (tpi):	
40	
Thread Size:	
0.250 inches	
Nonpile-up Contact Arrangement:	
1 pole, single throw, normally open, double make, momentary action single switch	ch unit
Contact Load Current Rating At Maximum Rated Voltage:	
100.000 milliamperes resistive dc and 100.000 milliamperes resistive ac	

Special Features:

Light emitting diode provided

NSN 5930-01-336-7686

Push Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Thread Series Designator:
Uns
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0