NSN 5930-01-336-8483

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-336-8483

| Body Style: |
|---|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Explosion proof and humidity resistant |
| Overall Length: |
| 3.050 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.750 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.530 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.100 inches |
| Actuator Width: |
| 0.530 inches |
| Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Port weapon 400 hz fail single actuator single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc and 115.0 ac |
| Mounting Surface To Terminal End Distance: |
| 2.950 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Full display lens |
| Contact Load Current Rating At Maximum Rated Voltage: |

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

Precious Material And Location:

inductive ac and 1.000 amperes lamp ac

Contact surfaces silver

NSN 5930-01-336-8483

Push Switch - Page 2 of 2



| Termina | I Type | And C | Juantity | , : |
|---------|--------|-------|----------|------------|
| | | | | |

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0