NSN 5930-01-336-8484

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-336-8484
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.050 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.530 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.530 inches
Actuator Color:
White single actuator
Actuator Inscription:
Stbd weapon 400 hz fail single actuator single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Contact Load Current Rating At Maximum Rated Voltage:
$7.500 \ amperes \ resistive \ dc \ and \ 5.000 \ amperes \ inductive \ dc \ and \ 1.000 \ amperes \ lamp \ dc \ and \ 5.000 \ amperes \ resistive \ ac \ and \ 3.500 \ amperes \ and \ 3.500 \ amperes \ ac \ and \ ac \ \ ac \ and \ ac \ an$
inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contact surfaces silver

NSN 5930-01-336-8484

Push Switch - Page 2 of 2



Terminal	Type	And	Qua	ntity:
ı Cı ıııııaı	1 4 10 0	Allu	wua	HILLEV.

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0