

| NSN 5930-01-336-9961 Rotary Switch - Page 1 of 2 | AeroBase Group |
|---|-------------------|
| View Online at https://aerobasegroup.com/nsn/5930-01-336-9961 | |
| Thread Class: | |
| 2a single mounting facility | |
| Overall Length: | |
| 3.874 inches | |
| Overall Height: | |
| 2.312 inches | |
| Overall Width: | |
| 1.968 inches | |
| Individual Section Quantity: | |
| 3 | |

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 3rd section rear

Throw Quantity:

12 3rd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

NSN 5930-01-336-9961

Rotary Switch - Page 2 of 2



| Thread Series Designato | TI | nread | Series | Design | ator |
|-------------------------|----|-------|--------|--------|------|
|-------------------------|----|-------|--------|--------|------|

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0